



PEX MULTI LAYER PIPES AND FITTINGS

COMPLY WITH BS EN ISO 21003-1:2008
 BS EN ISO 21003-3:2008
 BS EN ISO 21003-5:2008
 BS EN 12165:2016
 AS/NZS 4020:2005
 SS 375:2015



F6 PUSH-FIT



COMPONENTS:

Body

Made of Brass CW602N boosts corrosion resistance, eliminates processing stress, and stable.



Collet

PPSU, is stable, heat-resistant, and environment friendly. Inspection holes verify full tube insertion.



Collet Retainer

304 stainless steel corrosion resistant. Secures the fittings to prevent detachment.



Grab Ring

316 stainless steel, corrosion resistant. Inverted tooth securely holds the pipe in place.



Spacer

POM material provides high strength and impact resistance. Shrinks to grip preventing detachment.



Indicator Ring

HDPE, superior chemical and thermal stability. Easy visual inspection for proper depth and connection.



Seal Ring

High-quality EPDM resists weather and corrosion. Double seal prevents leakage.



Protection Cap

Safe and eco-friendly PP material, effectively blocking impurities and protecting the fitting.



STANDARD SPECIFICATION

Working Pressure	10 Bar
Working Temperature	0 ~ 60°C
Applications	Hot and cold potable water system, Underfloor heating system